

STATIONARY NG/LP PAINTED

STANDARD FEATURES

- Belt Driven General Triplex Pump
- 50 Ft. 3/8 Quick Coupled Hose
- Industrial Strength Electric Motor
- Sch 80 Black Pipe Heating Coil
- Hi Pressure Chemical
- Black Powder Coated Industrial Grade Frame
- Hi Limit Over Temp Protection
- Gun Control With 4 Ft. Lance
- Stainless Steel Coil Wrapper,
Control Panel and Flow Tank
- NG or LP Fired - Standing Pilot
- 24 VAC Controls



Options -

- EOST011 Auto OFF/Push Restart (Timer Shutdown)
- EOST012 Auto OFF/ON (Timer Shutdown)
- EOST015 Thermostat
- EOST016 Electronic Ignition
- EOST017 Hour Meter
- EOST010 10" Draft Diverter
- EOST018 Two Gun Operation

<u>MODEL</u>	<u>GPM</u>	<u>PSI</u>	<u>HP</u>	<u>VOLT</u>	<u>PH</u>	<u>AMPS</u>
64	3.8	2000	6	230	1	25
64-3	3.8	2000	5	230/460	3	16/8
643	4.0	3000	7 1/2	230	1	36
643-3	4.0	3000	7 1/2	230/460	3	25/15
65	5.0	1500	6	230	1	25
65-3	5.0	1500	5	230/460	3	16/8
66	5.0	2000	7 1/2	230	1	36
66-3	5.0	2000	7 1/2	230/460	3	25/15

DISTRIBUTED BY:

MANUFACTURED BY:

GCA-Largo Industries, Inc. • 40 Sevier Lane • P.O. Box 97 • Decaturville, TN 38329
TOLL FREE (800) 626-7384 • FAX (731) 852-2348 • www.gcalargo.com